

TECHNICAL DATA

Fluke 729 Automatic Pressure Calibrator



Key features

- Automatic pressure generation and regulation to 300 psi
- Configure procedures for pressure transmitters and switches
- Measure, source, and simulate 4 to 20 mA signals
- Troubleshoot and calibrate HART smart transmitters
- Automatically document test results

Product overview: Fluke 729 Automatic Pressure Calibrator

Portable automatic pressure calibrator simplifies pressure calibration

The Fluke 729 Automatic Pressure Calibrator has been designed specifically with process technicians in mind to simplify the pressure calibration process and provide faster, more accurate test results. Technicians know that calibrating pressure can be a time-consuming task, but the 729 makes it easier than ever with an internal electric pump that provides automatic pressure generation and regulation in an easy-to-use, rugged, portable package.

The ideal portable pressure calibrator, the 729 allows you to simply type in a target pressure, and the calibrator will automatically pump to the desired set-point. Then, internal fine adjustment control automatically stabilizes the pressure at the requested value.

The Fluke 729 can also automatically test multiple pressure test points and automatically document the results. Calibration is as easy as typing in the starting and ending pressure and the number of test points and tolerance level. The 729 does the rest.

Built-in HART communication capabilities enable HART transmitter mA adjustments, light HART configuration and the ability

to adjust to applied 0% and 100% values.

Upload and manage documented calibration results with [DPCTrack2™ Calibration Management Software](#), making it easy to manage your instrumentation, create scheduled tests and reports, and manage calibration data.

With three ranges to choose from, 30 psi (2 bar, 200 kPa), 150 psi (10 bar, 1 MPa) and 300 psi (20 bar, 2 MPa), Fluke 729 Automatic Pressure Calibrators are designed to perform when and where you need them.

Specifications: Fluke 729 Automatic Pressure Calibrator

| Pressure specification* |
|---|
| One-year specification 0.02% of full scale |
| Control specification 0.005% full scale minimum |
| *See manual for detailed specifications |

| Model | | |
|----------|------------------------------|--------------------------------|
| 729 30G | Psi range, resolution | -12.0000 to 30.0000 psi |
| | Bar range, resolution | -0.82737 to 2.06842 bar |
| | kPa range, resolution | -82.737 to 206.843 kPa |
| | Comment | No wireless communication |
| 729 150G | Psi range, resolution | -12.000 to 150.000 psi |
| | Bar range, resolution | -0.8273 to 10.3421 bar |
| | kPa range, resolution | -82.73 to 1034.21 kPa |
| | Comment | No wireless communication |
| 729 300G | Psi range, resolution | -12.000 to 300.000 psi |
| | Bar range, resolution | -0.8273 to 20.6843 bar |
| | kPa range, resolution | -82.73 to 2068.43 kPa |
| | Comment | No wireless communication |

| | | |
|--------------------|------------------------------|--|
| 729 30G FC | Psi range, resolution | -12.0000 to 30.0000 psi |
| | Bar range, resolution | -0.82737 to 2.06842 bar |
| | kPa range, resolution | -82.737 to 206.843 kPa |
| | Comment | Wireless communication for Fluke Connect |
| 729 150G FC | Psi range, resolution | -12.000 to 150.000 psi |
| | Bar range, resolution | -0.8273 to 10.3421 bar |
| | kPa range, resolution | -82.73 to 1034.21 kPa |
| | Comment | Wireless communication for Fluke Connect |
| 729 300G FC | Psi range, resolution | -12.000 to 300.000 psi |
| | Bar range, resolution | -0.8273 to 20.6843 bar |
| | kPa range, resolution | -82.73 to 2068.43 kPa |
| | Comment | Wireless communication for Fluke Connect |
| 729CN 200K | Psi range, resolution | -12.0000 to 30.0000 psi |
| | Bar range, resolution | -0.82737 to 2.06842 bar |
| | kPa range, resolution | -82.737 to 206.843 kPa |
| | Comment | For China, no wireless communication |
| 729CN 1M | Psi range, resolution | -12.000 to 150.000 psi |
| | Bar range, resolution | -0.8273 to 10.3421 bar |
| | kPa range, resolution | -82.73 to 1034.21 kPa |
| | Comment | For China, no wireless communication |

| | | |
|---------------|------------------------------|---|
| 729CN 2M | Psi range, resolution | -12.000 to 300.000 psi |
| | Bar range, resolution | -0.8273 to 20.6843 bar |
| | kPa range, resolution | -82.73 to 2068.43 kPa |
| | Comment | For China, no wireless communication |
| 729CN 200K FC | Psi range, resolution | -12.0000 to 30.0000 psi |
| | Bar range, resolution | -0.82737 to 2.06842 bar |
| | kPa range, resolution | -82.737 to 206.843 kPa |
| | Comment | For China, wireless communication for Fluke Connect |
| 729CN 1M FC | Psi range, resolution | -12.000 to 150.000 psi |
| | Bar range, resolution | -0.8273 to 10.3421 bar |
| | kPa range, resolution | -82.73 to 1034.21 kPa |
| | Comment | For China, wireless communication for Fluke Connect |
| 729CN 2M FC | Psi range, resolution | -12.000 to 300.000 psi |
| | Bar range, resolution | -0.8273 to 20.6843 bar |
| | kPa range, resolution | -82.73 to 2068.43 kPa |
| | Comment | For China, wireless communication for Fluke Connect |
| 729JP 200K | kPa range, resolution | -82.737 to 206.843 kPa |
| | Comment | For Japan, no wireless communication |
| 729JP 1M | kPa range, resolution | -82.73 to 1034.21 kPa |
| | Comment | For Japan, 1 MPa range, no wireless communication |
| 729JP 2M | kPa range, resolution | -82.73 to 2068.43 kPa |
| | Comment | For Japan, 2 MPa range, no wireless communication |

| | | |
|----------------------|------------------------------|---|
| 729JP 200K FC | kPa range, resolution | -82.737 to 206.843 kPa |
| | Comment | For Japan, wireless communication for Fluke Connect |
| 729JP 1M FC | kPa range, resolution | -82.73 to 1034.21 kPa |
| | Comment | For Japan, wireless communication for Fluke Connect |
| 729JP 2M FC | kPa range, resolution | -82.73 to 2068.43 kPa |
| | Comment | For Japan, wireless communication for Fluke Connect |

Electrical specification

All specifications are valid to 110% of range, except 24 mA source and simulate which are valid to 100% of range.

Ranges

| | |
|---------------------------------|-------------------|
| mA measure, source and simulate | 0 mA to 24 mA |
| Volts dc measure | 0 V dc to 30 V dc |

Resolution

| | |
|---|---|
| mA dc source, simulate and measure | 1 μ A |
| Voltage dc measurement | 1 mV |
| Accuracy | 0.01% \pm 2 LSD all ranges (at 23 °C \pm 5 °C) |
| Stability | 20 ppm of full scale /°C from -10 °C to +18 °C and 28 °C to +50 °C |
| mA simulate external voltage requirement | 12 V dc to 30 V dc |
| Loop compliance voltage | 24 V dc @ 20 mA |
| mA simulate external voltage requirement | 12 V dc to 30 V dc |
| Temperature measurement only/100 Ω Pt(385) RTD | -50 °C to 150 °C (-58 °F to 302 °F) |
| Temperature resolution | 0.01 °C (0.01 °F) |
| Temperature accuracy | \pm 0.1 °C (0.2 °F) \pm 0.25 °C (\pm 0.45 °F) combined uncertainty when using 720 RTD probe (optional accessory) |
| Drive capability | 1200 Ω without HART resistor, 950 Ω with internal HART resistor |

Mechanical specification

| | |
|--------------------|---|
| Size (HxWxL) | 7 x 27.94 x 17.27 cm (2.75 x 11 x 6.8 in) |
| Weight | 6.5 lbs., 2.95 kg |
| Ingress protection | IP54 |

| | |
|------------------------------------|---|
| Environmental specification | |
| Operating temperature | -10 °C to 50 °C for measurement, 0 °C to 50 °C for pressure control |
| Operating temperature with battery | -10 °C to 40 °C |
| Battery will only charge to 40 °C | |
| Storage temperature | -40 °C to 60 °C |
| Operating altitude | 3000 m |
| Storage altitude | 13000 m |
| Wireless (729 FC only) | |
| Radio frequency certification | FCC ID: T68-FBLE IC:6627A-FBLE |
| Wireless radio frequency range | 2412 MHz to 2462 MHz |

Ordering information

**FLK-729 30G**

Fluke 729 Automatic Pressure Calibrator 30 psi, 2 bar range, no wireless communication

FLK-729 150G

Fluke 729 Automatic Pressure Calibrator 150 psi, 10 bar range, no wireless communication

FLK-729 300G

Fluke 729 Automatic Pressure Calibrator 300 psi, 20 bar range, no wireless communication

FLK-729 30G FC

Fluke 729 Automatic Pressure Calibrator 30 psi, 2 bar range, includes wireless communication for Fluke Connect

FLK-729 150G FC

Fluke 729 Automatic Pressure Calibrator 150 psi, 10 bar range, includes wireless communication for Fluke Connect

FLK-729 300G FC

Fluke 729 Automatic Pressure Calibrator 300 psi, 20 bar range, includes wireless communication for Fluke Connect

FLK-729CN 200K**FLK-729CN 1M****FLK-729CN 2M**

FLK-729CN 200K FC

FLK-729CN 1M FC

FLK-729CN 2M FC

FLK-729PLUS 2M

FLK-729PLUS 1M

FLK-729PLUS 200K



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2023 Fluke Corporation.
Specifications subject to change without notice.
02/2023

**Modification of this document is not permitted
without written permission from Fluke Corporation.**