

# Fluke 753 Documenting Process Calibrator



## Key features

- Full-featured documenting process calibrator for calibrating and troubleshooting
- Measures volts, mA, RTDs, thermocouples, frequency, and ohms to test sensors, transmitters and other instruments
- Sources and simulate volts, mA, pressure, thermocouples, RTDs, frequency, ohms, and pressure to calibrate transmitters
- Powers transmitters during test using loop supply with simultaneous mA measurement

## Product overview: Fluke 753 Documenting Process Calibrator

### Fluke 753 Documenting Process Calibrator helps you work smarter and faster

The Fluke 753 is a powerful multifunction documenting calibrator that lets you download procedures, lists, and instructions created with software, and upload data for printing, archiving, and analysis. You'll find it does the work of several tools, with simultaneous source and measurement capabilities for all common process parameters. It sources, simulates, and measures pressure, temperature, and electrical signals in one rugged, hand-held calibration tool. It also automates calibration procedures, captures data for documentation, and helps you meet rigorous standards like ISO 9000, FDA, EPA, and OSHA regulations.

The 753 includes a USB interface and a USB communication cable to enable two-way communication with DPCTrack 2 and other instrumentation management applications. To create a seamless/paperless calibration management system consider adding [Fluke DPCTrack2 Calibration Management software](#) for use with your Fluke 753 and [754](#) or even legacy Fluke 743 and 744 calibrators.

### Other useful features:

- Measures and sources pressure using any of 50 [Fluke 700Pxx Pressure Modules](#)

- Allows you to create and run automated as-found/as-left procedures to satisfy quality programs or regulations, and record and document results
- Holds up to a full week of downloaded procedures and calibration results
- Offers many flexible features like autostep, custom units, user-entered values during test, one-point and two-point switch testing, square root DP flow testing, programmable measurement delay and more.
- Offers compatibility with DPCTrack2 and many other asset management software packages
- Bright white dual display for reading both sourced and measured parameters simultaneously
- Easy-to-use multi-lingual interface
- Gas gauge and rechargeable Li-Ion battery for 10 hour uninterrupted use
- Comes with three-year warranty and DPC/Track trial software

## Specifications: Fluke 753 Documenting Process Calibrator

Measurement Accuracy			
	Range /Resolution	1 Year	2 Years
Voltage DC	100.000 mV	0.02% + 0.005 mV	0.03% + 0.005 mV
	3.00000 V	0.02% + 0.00005 V	0.03% + 0.00005 V
	30.0000 V	0.02% + 0.0005 V	0.03% + 0.0005 V
	300.00 V	0.05% + 0.05 V	0.07% + 0.05 V
Voltage AC	<b>3.000 V (40 Hz to 500 Hz) / 0.001 V</b>	0.5% + 0.002 V	1.0% + 0.004 V
	30.00 V (40 Hz to 500 Hz) / 0.01 V	0.5% + 0.02 V	1.0% + 0.04 V
	300.0 V (40 Hz to 500 Hz) / 0.1 V	0.5% + 0.2 V	1.0% + 0.2 V
Current DC	<b>30.000 mA</b>	0.01% + 5 $\mu$ A	0.015% + 7 $\mu$ A
	110.00 mA	0.01% + 20 $\mu$ A	0.015% + 30 $\mu$ A
Resistance	<b>10.000 <math>\Omega</math></b>	0.05% + 50 m $\Omega$	0.07% + 70 m $\Omega$
	100.00 $\Omega$	0.05% + 50 m $\Omega$	0.07% + 70 m $\Omega$
	1.0000 k $\Omega$	0.05% + 500 m $\Omega$	0.07% + 0.5 $\Omega$
	10.000 k $\Omega$	0.1% + 10 $\Omega$	0.15% + 15 $\Omega$
Frequency	<b>1.00 to 110.00 Hz / 0.01 Hz</b>		0.05 Hz
	110.1 to 1100.0 Hz / 0.1 Hz		0.5 Hz
	1.101 to 11.000 kHz / 0.001 kHz		0.005 kHz
	11.01 to 50.00 kHz / 0.01 kHz		0.05 kHz
Source Accuracy			
		1 Year	2 Years
Voltage DC	<b>100.000 mV</b>	0.01% + 0.005 mV	0.015% + 0.005 mV
	1.00000 V	0.01% + 0.00005 V	0.015% + 0.0005 V
	15.0000 V	0.01% + 0.0005 V	0.015% + 0.0005 V

Current DC	<b>22.000 mA (source)</b>	0.01% + 0.003 mA	0.02% + 0.003 mA
	Current sink (simulate)	0.02% + 0.007 mA	0.04% + 0.007 mA
Resistance	<b>10.000 <math>\Omega</math></b>	0.01% + 10 m $\Omega$	0.015% + 15 m $\Omega$
	100.00 $\Omega$	0.01% + 20 m $\Omega$	0.015% + 30 m $\Omega$
	1.0000 k $\Omega$	0.02% + 0.2 $\Omega$	0.03% + 0.3 $\Omega$
	10.000 k $\Omega$	0.02% + 3 $\Omega$	0.03% + 5 $\Omega$
Frequency	<b>0.1 to 10.99 Hz</b>		0.01 Hz
	0.01 to 10.99 Hz		0.01 Hz
	11.00 to 109.99 Hz		0.1 Hz
	110.0 to 1099.9 Hz		0.1 Hz
	1.100 to 21.999 kHz		0.002 kHz
	22.000 to 50.000 kHz		0.005 kHz
<b>Technical Data</b>			
Data log functions	<b>Measure functions</b>	Voltage, current, resistance, frequency, temperature, pressure	
	Reading rate	1, 2, 5, 10, 20, 30, or 60 readings/minute	
	Maximum record length	8000 readings (7980 for 30 or 60 readings/minute)	
Ramp functions	<b>Source functions</b>	Voltage, current, resistance, frequency, temperature	
	Rate	4 steps/second	
	Trip detect	Continuity or voltage (continuity detection not available when sourcing current)	
Loop power function	<b>Voltage</b>	Selectable, 26 V	
	Accuracy	10%, 18 V minimum at 22 mA	
	Maximum current	25 mA, short circuit protected	
	Maximum input voltage	50 V DC	
Step functions	<b>Source functions</b>	Voltage, current, resistance, frequency, temperature	
	Manual step	Selectable step, change with arrow buttons	
	Autostep	Fully programmable for function, start delay, stepvalue, time per step, repeat	
<b>Environmental Specifications</b>			
Operating temperature	-10°C to +50°C		
Storage temperature	-20°C to +60°C		
Dust/water resistance	Meets IP52, IEC 529		
Operating altitude	3000 m above mean sea level (9842 ft)		
<b>Safety Specifications</b>			
Agency approvals	CAN/CSA C22.2 No 1010.1-92, ASNI/ISA S82.01-1994, UL3111, and EN610-1:1993		
<b>Mechanical and General Specifications</b>			

Size	136 x 245 x 63 mm (5.4 x 9.6 x 2.5 in)
Weight	1.2 kg (2.7 lb)
Batteries	Internal Battery Pack Li-ion: 7.2 V, 4400 mAh, 30 Wh
Battery life	> 8 hours typical
Battery replacement	Via snap-shut door without opening calibrator; no tools required
Side port connections	Pressure module connector
	USB Connector to interface to your PC
	Connection for optional battery charger/eliminator
Data storage capacity	1 week of calibration procedures results
90 day specifications	The standard specification interval for the 750 Series are 1 and 2 years.
	Typical 90 day measurement and source accuracy can be estimated by dividing the one year "% of reading" or "% of output" specifications by 2.
	Floor specifications, expressed as "% of full scale" or "counts" or "ohms" remain constant.

#### Temperature, Resistance Temperature Detectors

Degrees or % of reading - Type (α)	Range °C	Measure °C <sup>1</sup>	
		1 year	2 year
100 Ω Pt (385)	-200 to 100 100 to 800	0.07°C 0.02% + 0.05°C	0.14°C 0.04% + 0.10°C
200 Ω Pt (385)	-200 to 100 100 to 630	0.07°C 0.02% + 0.05°C	0.14°C 0.04% + 0.10°C
500 Ω Pt (385)	-200 to 100 100 to 630	0.07°C 0.02% + 0.05°C	0.14°C 0.04% + 0.10°C
1000 Ω Pt (385)	-200 to 100 100 to 630	0.07°C 0.02% + 0.05°C	0.14°C 0.04% + 0.10°C
100 Ω Pt (3916)	-200 to 100 100 to 630	0.07°C 0.02% + 0.05°C	0.14°C 0.04% + 0.10°C
100 Ω Pt (3926)	-200 to 100 100 to 630	0.08°C 0.02% + 0.06°C	0.16°C 0.04% + 0.12°C
10 Ω Cu (427)	-100 to 260	0.2°C	0.4°C
120 Ω Ni (672)	-80 to 260	0.1°C	0.2°C
Source current	Source °C		Allowable current <sup>2</sup>
	1 year	2 year	
1 mA	0.05°C 0.0125% + 0.04°C	0.10°C 0.025% + 0.08°C	0.1 mA to 10 mA
500 μA	0.06°C 0.017% + 0.05°C	0.12°C 0.034% + 0.10°C	0.1 mA to 1 mA
250 μA	0.06°C 0.017% + 0.05°C	0.12°C 0.034% + 0.10°C	0.1 mA to 1 mA

150 $\mu$ A	0.06°C 0.017% + 0.05°C	0.12°C 0.034% + 0.10°C	0.1 mA to 1 mA
1 mA	0.05°C 0.0125% + 0.04°C	0.10°C 0.025% + 0.08°C	0.1 mA to 10 mA
1 mA	0.05°C 0.0125% + 0.04°C	0.10°C 0.025% + 0.08°C	0.1 mA to 10 mA
3 mA	0.2°C	0.4°C	0.1 mA to 10 mA
1 mA	0.04°C	0.08°C	0.1 mA to 10 mA

1. For two and three-wire RTD measurements, add 0.4°C to the specifications.
2. Supports pulsed transmitters and PLCs with pulse times as short as 1 ms

### Temperature, Thermocouples

Type	Source °C	Measure °C		Source °C	
		1 year	2 years	1 year	2 years
E	<b>-250 to -200</b>	1.3	2.0	0.6	0.9
	-200 to -100	0.5	0.8	0.3	0.4
	-100 to 600	0.3	0.4	0.3	0.4
	600 to 1000	0.4	0.6	0.2	0.3
N	<b>-200 to -100</b>	1.0	1.5	0.6	0.9
	-100 to 900	0.5	0.8	0.5	0.8
	900 to 1300	0.6	0.9	0.3	0.4
J	<b>-210 to -100</b>	0.6	0.9	0.3	0.4
	-100 to 800	0.3	0.4	0.2	0.3
	800 to 1200	0.5	0.8	0.3	0.3
K	<b>-200 to -100</b>	0.7	1.0	0.4	0.6
	-100 to 400	0.3	0.4	0.3	0.4
	400 to 1200	0.5	0.8	0.3	0.4
	1200 to 1372	0.7	1.0	0.3	0.4
T	<b>-250 to -200</b>	1.7	2.5	0.9	1.4
	-200 to 0	0.6	0.9	0.4	0.6
	0 to 400	0.3	0.4	0.3	0.4
B	<b>600 to 800</b>	1.3	2.0	1.0	1.5
	800 to 1000	1.0	1.5	0.8	1.2
	1000 to 1820	0.9	1.3	0.8	1.2
R	<b>-20 to 0</b>	2.3	2.8	1.2	1.8
	0 to 100	1.5	2.2	1.1	1.7
	100 to 1767	1.0	1.5	0.9	1.4

S	<b>-20 to 0</b>	2.3	2.8	1.2	1.8
	0 to 200	1.5	2.1	1.1	1.7
	200 to 1400	0.9	1.4	0.9	1.4
	1400 to 1767	1.1	1.7	1.0	1.5
C	<b>0 to 800</b>	0.6	0.9	0.6	0.9
	800 to 1200	0.8	1.2	0.7	1.0
	1200 to 1800	1.1	1.6	0.9	1.4
	1800 to 2316	2.0	3.0	1.3	2.0
L	<b>-200 to -100</b>	0.6	0.9	0.3	0.4
	-100 to 800	0.3	0.4	0.2	0.3
	800 to 900	0.5	0.8	0.2	0.3
U	<b>-200 to 0</b>	0.6	0.9	0.4	0.6
	0 to 600	0.3	0.4	0.3	0.4
BP	<b>0 to 1000</b>	1.0	1.5	0.4	0.6
	1000 to 2000	1.6	2.4	0.6	0.9
	2000 to 2500	2.0	3.0	0.8	1.2
XK	<b>-200 to 300</b>	0.2	0.3	0.2	0.5
	300 to 800	0.4	0.6	0.3	0.6

## Ordering information



### **Fluke 753**

Fluke 753 Documenting Process Calibrator

Includes:

- BC7240 battery charger
- Li-on BP7240 battery pack
- DPCTrack 2™ Sample Software
- Instruction manual
- NIST-traceable calibration report and data
- Three sets of TP220 test probes with three sets of "extended tooth" alligator clips
- Two sets AC280 hook clips
- C799 Soft Field Case
- USB communication cable



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2023 Fluke Corporation.  
Specifications subject to change without notice.  
02/2023

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**