

Technical Data for IS-Max ISMCQ-Series Mass Flow Controllers

10 sccm full scale through 2 SLPM full scale

Standard specifications. Consult Alicat for available options.



+1 (888) 290-6060
alicat.com/ismc

Ex Document

CERTIFICATIONS	MARKING	CERTIFICATE
ATEX	II 1G Ex ia IIC T4 Ga $T_{amb} -20^{\circ}\text{C to }+70^{\circ}\text{C}$	DEKRA 22ATEX0075X
IECEX	Ex ia IIC T4 Ga $T_{amb} -20^{\circ}\text{C to }+70^{\circ}\text{C}$	IECEX DEK 22.0078 X

SENSOR AND CONTROL PERFORMANCE ¹	
Mass flow accuracy ²	$\pm 0.6\%$ of reading or $\pm 0.1\%$ of full scale, whichever is greater
Flow repeatability (2σ)	$\pm 0.1\%$ of full scale
Pressure accuracy ²	Above 1 atm: $\pm 0.5\%$ of reading Below 1 atm: ± 0.07 PSIA
Steady state control range	0.5 – 100% of full scale (200:1 turndown ratio)
Operating pressure	11.5 – 320 PSIA
Pressure sensitivity	Mass flow zero shift: $\pm 0.01\%$ of full scale per atm from tare pressure Mass flow span shift: $\pm 0.1\%$ of reading per atmosphere from calibration conditions
Temperature sensitivity	Mass flow zero shift: $\pm 0.01\%$ of full scale per $^{\circ}\text{C}$ from tare temperature, per atm Mass flow span shift: $\pm 0.01\%$ of reading per $^{\circ}\text{C}$ from 25°C , per atm
Temperature accuracy	$\pm 0.75^{\circ}\text{C}$
Relative humidity accuracy ³	$\pm 1.8\%$ RH at $+23^{\circ}\text{C}$ (0 % RH to 90% RH)
Relative humidity temperature sensitivity ³	0.05% RH/ $^{\circ}\text{C}$ (0°C to $+60^{\circ}\text{C}$)
Operating temperature range ⁴	$-20 - 70^{\circ}\text{C}$ (ambient and gas)
Valve function	Normally closed
Totalizer volume uncertainty	$\pm 0.1\%$ of reading additional uncertainty
Sensor response time	< 1 ms
Typical control response time	As fast as 100 ms (T63), flow rate dependent, user-adjustable
Typical indication response time	< 10 ms, flow rate dependent
Typical warm-up time	< 1 s

¹ Flow rate and pressure drop vary depending on process gas.

² Stated accuracy is after tare (for mass flow), under equilibrium conditions, includes repeatability and linearity.

³ Relative humidity sensor is an optional feature.

Technical Data for IS-Max ISMCQ-Series Mass Flow Controllers

10 sccm full scale through 2 SLPM full scale

Standard specifications. Consult Alicat for available options.



+1 (888) 290-6060
alicat.com/ismc

Ex Document

MECHANICAL	
Wetted materials	316L, 303, 430FR stainless steel, FKM or EPDM as needed for some gases alumina ceramic, brass, glass, gold, heat-cured epoxy, heat-cured silicone rubber, polyamide, silicon
Maximum pressure	Damage possible above 400 PSIA common mode pressure. Damage possible by rapid pressure change above 75 PSI differential pressure.
Relative humidity range	0 – 95%, non-condensing
Ingress protection	IP66 rating Dust-tight and protected against strong jets of water
Mounting orientation sensitivity	None
Mounting holes	4× 6-32 UNC threaded ↓ 0.276" [7.01 mm]

POWER AND COMMUNICATIONS	
Digital input and output options	RS-232, RS-485, Modbus RTU and Alicat ASCII protocols
Digital data update rate	40 Hz at 19200 baud
Analog input and output options	4 – 20 mA
Analog data update rate	1 kHz
Analog signal accuracy	± 0.1% of full scale additional uncertainty
Interactive display	Monochrome LCD with integrated touchpad and backlight; simultaneously displays mass flow, volumetric flow, temperature, setpoint, valve drive %, gauge pressure, and absolute pressure
Display update rate	10 Hz
Electrical connection options	DB-15
Power requirements	See DOC-MANUAL-IS-SAFEINSTALLATION

FEATURES	
STP reference conditions	25 °C and 1 atm (default), user-configurable
NTP reference conditions	0 °C and 1 atm (default), user-configurable
Gas Select™	98 user-selectable gases stored internally. Each gas optimized to match NIST's REFPROP 10 gas property calculations across the operating temperature and pressure ranges for highest accuracy.
COMPOSER™	20 user-definable gas mixes. Each mix may have up to 5 gases with 0.01% composition resolution.
Multivariate process measurements	Volumetric flow, mass flow, absolute pressure, gauge pressure, barometric pressure, temperature, totalizer Optional: relative humidity
Autotune	Automatically improve the control performance of the valve and tune the control parameters of the device for your application
Totalizer and batch dispensing	Measure the total accumulated mass of a particular gas (or gas mixture) that has flowed in a process. The totalizer function in controllers can also be used to dispense batches of set amounts of gas.

RANGE-SPECIFIC TECHNICAL DATA		
Full scale flow	Pressure drop at full scale ⁴	Default process connections ⁵
10 sccm	1.5 PSID	M5 x 0.8mm female
20 sccm	2.0 PSID	M5 x 0.8mm female
50 sccm	6.0 PSID	1/8" NPT female
100 sccm	20.0 PSID	1/8" NPT female
200 sccm	1.5 PSID	1/8" NPT female
500 sccm	4.2 PSID	1/8" NPT female
1 SLPM	14.3 PSID	1/8" NPT female
2 SLPM	2.3 PSID	1/8" NPT female

⁴ When venting air to atmosphere and valve circuit powered by the Eaton 9493-PS-C11 at an ambient temperature of ~ 30°C

⁵ Consult Alicat for available connection options, such as: compression, face seal, push-to-connect, BSPP, SAE, or Swagelok®-compatible (VCO® and VCR®).

Ex Document. Any revisions must be submitted for review and approval by an Ex Appointee.

Technical Data for IS-Max ISMCQ-Series Mass Flow Controllers

10 sccm full scale through 2 SLPM full scale


Standard specifications. Consult Alicat for available options.

Ex Document




+1 (888) 290-6060
alicat.com/ismc

Representative Example



100 SCCM



○ Mounting holes

4X 6-32 UNC ↓ 0.276in [7.01mm]

DIMENSIONS										WEIGHT
Full scale flow	Width	Depth	Height	A	B	C	E	F	G	
10 SCCM – 2 SLPM	5.75"	1.50"	7.05"	0.50"	0.75"	0.15"	1.35"	1.25"	3.00"	≈ 5.0 lb
	146.1 mm	38.1 mm	179.1 mm	12.7 mm	19.1 mm	3.9 mm	34.2 mm	31.8 mm	76.2 mm	≈ 2.3 kg

Ex Document. Any revisions must be submitted for review and approval by an Ex Appointee.