



Hand Pump Series

The Meriam Calibration Pump MH-10KT uses a fully adjustable stroke control to allow for fast priming or filling of test systems. This gives the operator the ability to switch as needed to a smaller stroke for easier pumping at high pressure.

MH-10KT Hydraulic Calibration Pump

Features

Contoured cushion handles
Patented protective cage around vent knob
Priming feature
Patented triple filtration (prevents pump failure caused by dirt)
A non-oil based lubricant is used on all moving parts
Built in pressure relief valve (prevents over pressurizing)
Shatter proof reservoir
Oversized check valves for smooth controlled operation
2 year warranty (includes dropping)
Includes: black padded canvas case, 3ft high pressure hose, fittings, adaptors, test point and (3) spare filters.

Specifications

0 - 10,000 psi (700 Bar)
Compatible with most hydraulic fluids, oils and water Connections (2 ports) 1/4 inch NPT / BSP
Weight 3lbs
Made in the USA

Additional Information

The Meriam Calibration Pump MH10K uses a fully adjustable stroke control to allow for fast priming or filling of test systems. This gives the operator the ability to switch as needed to a smaller stroke for easier pumping at high pressures.

Options

Model# M-10FW Additional spare filters (3) and (2) spare rubber bonded washers.
Meriam Merigauge Digital Pressure Gauge, 4 1/2" digit LCD gauge, battery operated, pipe mount via 1/4" MNPT 316 stainless steel stem, 304 stainless steel NEMA 4 rated housing, ranges 0 to 6000 PSIG. Please visit our website for more information.
Note: Kits, hoses and fittings can be customized upon request.

Additional Products



MP-100KT Calibration Pump

Features

Delrin plastic handle prevents body heat transfer
Oversized check valves for smooth controlled operation
Mash proof vent valve (No Needle Valve)
A patented non-oil based lubricant is used on all moving parts
Dual O-Rings on all pistons to ensure zero leakage
2 year warranty (includes dropping)
Includes: A black padded canvas case, 2ft non-stretch hose, fittings and stainless steel analog gauge 2" 1/2 w/ protective rubber boot.

Specifications

MV-100 0-28"Hg (depends on barometric pressure)
MP-100 0 to 100 psi (including and not limited to an inch of water) Connections (2 ports) 1/8 inch NPT
Weight 1.5lbs
2ft hose and 1/4 inch fitting
Made in the USA

Options

Meriam Merigauge Digital Pressure Gauge, 4 1/2" digit LCD gauge, battery operated, pipe mount via 1/4" MNPT 316 stainless steel stem, 304 stainless steel NEMA 4 rated housing, ranges 0 to 6000 PSIG. Please visit our website for more information.



M-600KT shown with optional Merigauge Digital Pressure Gauge

M-600KT Combo Pneumatic Calibration

Features

Contoured cushion handles
Oversized check valves for smooth controlled operation
Mash proof vent valve (No Needle Valve)
A patented non-oil based lubricant is used on all moving parts
Dual O-Rings on all pistons to ensure zero leakage
2 year warranty (includes dropping)
Includes: A black padded canvas case, 2ft non-stretch hose, fittings and Meriam stainless steel analog gauge 2" 1/2 w/ protective rubber boot.

Specifications

Vacuum 28" Hg to pressure 600psi (combination pump) Compatible with all gauges and calibrators
Connections (2 ports) 1/4 inch and 1/8" inch NPT/
BSP Weight 2 lbs
Made in the USA

Options

Meriam Merigauge Digital Pressure Gauge, 4 1/2" digit LCD gauge, battery operated, pipe mount via 1/4" MNPT 316 stainless steel stem, 304 stainless steel NEMA 4 rated housing, ranges 0 to 6000 PSIG. Please visit our website for more information.

